

运行范围

- 喷灌强度:0.37至1.14英寸/小时 (9至29毫米/小时)
- 射程:39至65英尺 (11.9至19.8米)
- 压力:30至90磅/平方英寸 (2.1至6.2巴)
- 流量:2.9至21.7加仑/分钟 (0.66至4.93立方米/小时; 10.8至82.2升/分钟)

技术参数

- 1英寸 (26/34) NPT内螺纹或BSP螺纹接口
- SAM 止溢装置可承受坡度差距10 英尺 (3.1 米)
- 雨帘喷嘴:04-黑色;06-浅蓝色;08-深绿色;10-灰色;12-米色;14-浅绿色;16-深棕色;18-深蓝色
- 喷嘴的喷射仰角为25°

尺寸

- 整体高度:8½英寸 (21.6厘米)
 - 弹出高度:4英寸 (10.2厘米)
 - 外露直径:2英寸 (5.1厘米)
- 注意: 顶盖至喷嘴中心位置的距离为弹出高度。
收缩状态的喷头长度为整体高度。

型号

- F4-FC:全圆
 - F4-PC:扇形
 - F4-FC-NP:全圆, 非饮用水顶盖
 - F4-PC-NP:扇形, 非饮用水顶盖
 - F4-FC-SS:全圆, 不锈钢升降柱
 - F4-FC-SS:扇形, 不锈钢升降柱
 - F4-FC-SS-HS:全圆, 不锈钢升降柱, 高速旋转
 - F4-PC-SS-HS:扇形, 不锈钢升降柱, 高速旋转
 - F4-FC-SS-NP:全圆, 不锈钢升降柱, 非饮用水顶盖
 - F4-PC-SS-NP:扇形, 不锈钢升降柱, 非饮用水顶盖
- 注意: : 所有型号都具有BSP螺纹。



Falcon® 6504雨帘喷嘴

Falcon® 6504喷嘴性能参数

压力 磅/平方英寸	喷嘴	射程 英尺	流量 加仑/分钟	■ 喷灌强度 英寸/小时	▲ 喷灌强度 英寸/小时
30	● 4	39	2.9	0.37	0.42
	● 6	43	4.2	0.44	0.50
40	● 4	41	3.3	0.38	0.44
	● 6	45	4.9	0.47	0.54
	● 8	49	6.6	0.53	0.61
	● 10	51	8.1	0.60	0.69
	● 12	53	9.7	0.66	0.77
	● 14	55	11.3	0.72	0.83
	● 16	55	12.6	0.80	0.93
50	● 18	59	13.7	0.76	0.87
	● 4	41	3.7	0.42	0.49
	● 6	49	5.5	0.44	0.51
	● 8	51	7.4	0.55	0.63
	● 10	53	9.1	0.62	0.72
	● 12	55	11.0	0.70	0.81
60	● 14	59	12.7	0.70	0.81
	● 16	61	14.3	0.74	0.85
	● 18	59	15.4	0.85	0.98
	● 4	41	4.0	0.46	0.53
	● 6	47	6.0	0.52	0.60
	● 8	51	8.2	0.61	0.70
	● 10	55	10.0	0.64	0.73
70	● 12	57	12.2	0.72	0.83
	● 14	61	14.0	0.72	0.84
	● 16	63	15.7	0.76	0.88
	● 18	63	17.1	0.83	0.96
	● 4	41	4.4	0.50	0.58
	● 6	49	6.3	0.51	0.58
	● 8	51	8.9	0.66	0.76
80	● 10	57	10.8	0.64	0.74
	● 12	59	13.2	0.73	0.84
	● 14	61	15.2	0.79	0.91
	● 16	63	16.9	0.82	0.95
	● 18	65	18.3	0.83	0.96
	● 4	43	4.6	0.48	0.55
	● 6	49	6.9	0.55	0.64
90	● 8	53	9.4	0.64	0.74
	● 10	55	11.6	0.74	0.85
	● 12	61	14.0	0.72	0.84
	● 14	61	16.2	0.84	0.97
	● 16	63	18.1	0.88	1.01
	● 18	65	19.6	0.89	1.03
	● 18	65	21.7	0.99	1.14

以半圆模式运行, 测取喷灌强度。

■ 正方形布置, 间距基于喷洒直径的50%

▲ 三角形布置, 间距基于喷洒直径的50%

性能参数在无风情况下测取。

性能参数取自符合ASAE标准的测试, ASAE S398.1。

完整的ASAE测试认证声明, 请参阅第224页。

Falcon® 6504喷嘴性能参数							公制
压力巴	喷嘴	射程米	流量 立方米/小时	流量 升/分钟	■ 喷灌强度 毫米/小时	▲ 喷灌强度 毫米/小时	
2.1	● 4	11.9	0.66	10.98	9	11	
	● 6	13.1	0.95	15.90	11	13	
2.5	● 4	12.3	0.72	11.92	10	11	
	● 6	13.5	1.05	17.56	12	13	
	● 8	14.9	1.50	25.20	13	16	
	● 10	15.5	1.84	30.60	15	18	
	● 12	16.2	2.20	36.60	17	19	
	● 14	16.8	2.57	42.60	18	21	
	● 16	16.8	2.86	47.40	20	24	
3.0	● 18	18.0	3.11	51.60	19	22	
	● 4	12.5	0.78	13.02	10	12	
	● 6	14.1	1.16	19.34	12	13	
	● 8	15.1	1.56	26.04	14	16	
	● 10	15.8	1.92	31.99	15	18	
	● 12	16.4	2.31	38.44	17	20	
	● 14	17.2	2.68	44.63	18	21	
3.5	● 16	17.4	3.00	49.95	20	23	
	● 18	18.0	3.25	54.11	20	23	
	● 4	12.5	0.85	14.09	11	13	
	● 6	14.9	1.26	20.96	11	13	
	● 8	15.5	1.69	28.24	14	16	
	● 10	16.2	2.08	34.70	16	18	
	● 12	16.8	2.52	41.98	18	21	
4.0	● 14	18.0	2.91	48.45	18	21	
	● 16	18.6	3.27	54.53	19	22	
	● 18	18.1	3.53	58.78	22	25	
	● 4	12.5	0.89	14.91	11	13	
	● 6	14.4	1.34	22.33	13	15	
	● 8	15.5	1.83	30.44	15	17	
	● 10	16.6	2.23	37.17	16	19	

Falcon® 6504喷嘴性能参数							公制
压力巴	喷嘴	射程米	流量 立方米/小时	流量 升/分钟	■ 喷灌强度 毫米/小时	▲ 喷灌强度 毫米/小时	
4.5	● 4	12.5	0.96	15.94	12	14	
	● 6	14.6	1.40	16.72	13	15	
	● 8	15.5	1.95	32.43	16	19	
	● 10	17.1	2.37	39.44	16	19	
	● 12	17.7	2.89	48.17	18	21	
	● 14	18.6	3.32	55.38	19	22	
	● 16	19.2	3.71	61.82	20	23	
5.0	● 18	19.5	4.03	67.12	21	24	
	● 4	12.7	1.01	16.84	13	15	
	● 6	14.9	1.47	15.08	13	15	
	● 8	15.7	2.05	34.16	17	19	
	● 10	17.2	2.50	41.64	17	19	
	● 12	18.1	3.04	50.72	19	21	
	● 14	18.6	3.51	58.49	20	23	
5.5	● 16	19.2	3.91	65.11	21	24	
	● 18	19.8	4.23	70.51	22	25	
	● 4	13.1	1.04	17.39	12	14	
	● 6	14.9	1.56	25.79	14	16	
	● 8	16.1	2.13	35.54	16	19	
	● 10	16.8	2.63	43.84	19	22	
	● 12	18.6	3.18	52.92	18	21	
6.0	● 14	18.6	3.67	61.23	21	25	
	● 16	19.2	4.10	68.40	22	26	
	● 18	19.8	4.44	74.07	23	26	
	● 18	19.8	4.79	79.77	24	28	
	● 18	19.8	4.93	82.13	25	29	

以半圆模式运行，测取喷灌强度。

■ 正方形布置，间距基于喷洒直径的50%

▲ 三角形布置，间距基于喷洒直径的50%

性能参数在无风情况下测取。

性能参数取自符合ASAE标准的测试，ASAE S398.1。
完整的ASAE测试认证声明，请参阅第224页。

高速Falcon® 6504喷嘴性能参数					
压力 磅/平方英寸	喷嘴	射程 英尺	流量 加仑/分钟	■ 喷灌强度 英寸/小时	▲ 喷灌强度 英寸/小时
30	● 4	37	3.0	0.42	0.49
	● 6	39	4.3	0.54	0.63
40	● 4	41	3.5	0.40	0.46
	● 6	43	6.0	0.62	0.72
	● 8	47	6.6	0.58	0.66
	● 10	47	8.1	0.71	0.82
	● 12	49	9.9	0.79	0.92
	● 14	53	11.4	0.78	0.90
	● 16	51	12.6	0.93	1.08
50	● 18	53	13.9	0.95	1.10
	● 4	41	3.7	0.42	0.49
	● 6	45	5.6	0.53	0.62
	● 8	49	7.5	0.60	0.69
	● 10	49	9.2	0.74	0.85
	● 12	53	11.2	0.77	0.89
	● 14	53	12.9	0.88	1.02
60	● 16	53	14.3	0.98	1.13
	● 18	55	15.6	0.99	1.15
	● 4	41	4.2	0.48	0.56
	● 6	45	6.2	0.59	0.68
	● 8	47	8.3	0.72	0.84
	● 10	49	10.2	0.82	0.94
	● 12	53	12.4	0.85	0.98
70	● 14	53	14.2	0.97	1.12
	● 16	55	15.7	1.00	1.15
	● 18	59	17.2	0.95	1.10
	● 4	41	4.2	0.48	0.56

高速Falcon® 6504喷嘴性能参数					
压力 磅/平方英寸	喷嘴	射程 英尺	流量 加仑/分钟	■ 喷灌强度 英寸/小时	▲ 喷灌强度 英寸/小时
70	● 4	41	4.6	0.53	0.61
	● 6	43	6.7	0.70	0.81
	● 8	49	9.0	0.72	0.83
	● 10	51	11.1	0.82	0.95
	● 12	55	13.5	0.86	0.99
	● 14	53	15.3	1.05	1.21
	● 16	57	17.1	1.01	1.17
80	● 18	59	18.6	1.03	1.19
	● 4	39	4.9	0.62	0.72
	● 6	43	7.1	0.74	0.85
	● 8	51	9.7	0.72	0.83
	● 10	49	11.9	0.95	1.10
	● 12	55	14.4	0.92	1.06
	● 14	53	16.5	1.13	1.31
90	● 16	59	18.4	1.02	1.18
	● 18	59	20.0	1.11	1.28
	● 4	41	4.9	0.62	0.72
	● 6	43	7.1	0.74	0.85

以半圆模式运行，测取喷灌强度。

■ 正方形布置，间距基于喷洒直径的50%

▲ 三角形布置，间距基于喷洒直径的50%

性能参数在无风情况下测取。

性能参数取自符合ASAE标准的测试，ASAE S398.1。

完整的ASAE测试认证声明，请参阅第224页。

高速Falcon® 6504喷嘴性能参数							公制
压力巴	喷嘴	射程米	流量 立方米/小时	流量 升/分钟	■ 喷灌强度 毫米/小时	▲ 喷灌强度 毫米/小时	
2.1	● 4	11.3	0.68	11.35	11	12	
	● 6	11.9	0.98	15.90	14	16	
2.5	● 4	12.0	0.75	12.54	10	12	
	● 6	12.7	1.22	20.16	15	18	
	● 8	14.2	1.49	25.20	15	17	
	● 10	14.2	1.83	30.60	18	21	
	● 12	14.8	2.24	37.20	20	24	
	● 14	16.0	2.58	43.20	20	23	
	● 16	15.4	2.85	47.40	24	28	
3.0	● 18	16.0	3.15	52.80	24	28	
	● 4	12.5	0.81	13.51	10	12	
	● 6	13.3	1.33	22.18	15	17	
	● 8	14.5	1.57	26.18	15	17	
	● 10	14.5	1.93	32.12	18	21	
	● 12	15.4	2.35	39.20	20	23	
	● 14	16.2	2.71	48.09	21	24	
3.5	● 16	15.8	3.00	49.95	24	28	
	● 18	16.4	3.29	54.87	25	28	
	● 4	12.5	0.85	14.15	11	13	
	● 6	13.7	1.28	21.37	14	16	
	● 8	14.9	1.72	28.62	16	18	
	● 10	14.9	2.11	35.11	19	22	
	● 12	16.2	2.56	42.74	20	23	
4.0	● 14	16.2	2.95	49.20	23	26	
	● 16	16.2	3.27	54.53	25	29	
	● 18	16.9	3.57	59.51	25	29	
	● 4	12.5	0.93	15.52	12	14	
	● 6	13.7	1.38	23.02	15	17	

高速Falcon® 6504喷嘴性能参数							公制
压力巴	喷嘴	射程米	流量 立方米/小时	流量 升/分钟	■ 喷灌强度 毫米/小时	▲ 喷灌强度 毫米/小时	
4.5	● 4	12.5	1.00	16.69	13	15	
	● 6	13.4	1.48	24.46	16	19	
	● 8	14.6	1.97	32.81	18	21	
	● 10	15.3	2.42	40.40	21	24	
	● 12	16.5	2.95	49.13	22	25	
	● 14	16.2	3.36	55.94	26	30	
	● 16	17.1	3.73	62.22	26	30	
5.0	● 18	18.0	4.07	67.89	25	29	
	● 4	12.3	1.06	17.70	14	16	
	● 6	13.1	1.56	25.74	18	21	
	● 8	15.1	2.08	34.73	18	21	
	● 10	15.4	2.57	42.78	22	25	
	● 12	16.8	3.12	51.96	22	26	
	● 14	16.2	3.54	59.06	27	31	
5.5	● 16	17.5	3.96	65.96	26	30	
	● 18	18.0	4.30	71.74	27	31	
	● 4	11.9	1.11	18.52	16	18	
	● 6	13.1	1.61	26.84	19	22	
	● 8	15.5	2.20	36.65	18	21	
	● 10	14.9	2.70	44.97	24	28	
	● 12	16.8	3.27	54.43	23	27	
6.0	● 14	16.2	3.74	62.35	29	33	
	● 16	18.0	4.17	69.53	26	30	
	● 18	18.0	4.53	75.58	28	32	
	● 18	18.4	4.75	79.16	28	32	
	● 18	18.6	4.84	80.62	28	32	

以半圆模式运行，测取喷灌强度。

■ 正方形布置，间距基于喷洒直径的50%

▲ 三角形布置，间距基于喷洒直径的50%

性能参数在无风情况下测取。

性能参数取自符合ASAE标准的测试，ASAE S398.1。

完整的ASAE测试认证声明，请参阅第224页。