

Rain Bird® 952 系列 全圓/可調高爾夫噴頭

技術參數

射程範圍:

- 70'- 101'(21.3m - 31.8m)

流量範圍:

- 19.7 to 54.5 gpm (1.24 to 3.44 l/s)
(4.43 to 12.38 m³/h)

可調角度:

- 全圓模式360°, 可調模式 30° to 345°

可選模式:

- E: 電控
- IC: 集成控制
- SAM: 止溢型

最大承壓:

- Models E&IC: 150 psi (10.3 bars)
- Model SAM: 100 psi (6.9 bars)

工作壓力:

- Models E&IC: 60 to 100 psi (4.1 to 6.9 bars)

出廠設定:

- Models E&IC 設定為 70 或 80 psi (4.8 and 5.5 bars)

噴頭尺寸:

- 高度: 13.4"(34.0 cm)
- 噴頭彈起高度: 2.6"(6.6 cm)
- 頂部直徑: 7.0"(17.8 cm)

快速調節技術

通過調節螺絲轻松調整弧度, MemoryArc® 功能保留了兩個部分圓弧設置, 因此可以在几秒钟內在完整和部分圓弧操作之間切換。



第一步: 設置主轉子角度



第二步: 調節全圓/可調螺絲調整噴頭模式



第三步: 將轉子旋转到圓弧A或圓弧B設置, 然後設置為零件圓。在完整圓和可調設置之間進行更改時, 無需重置圓弧。



(continued)

噴嘴參數:

- 常規射角: 25°
- 低仰角: 17°

進水口尺寸:

- Models E, IC, SAM: 1.5 (3.8mm) ACME 陰螺紋

止溢高度:

- SAM: 17'(5.2m) 高程

轉速:

- 180° 以內 ≤ 100 秒; 參考標準為 80 秒

最大射流高度:

- 常規射流: 22'(6.7m)
- 低仰角射流: 12'(3.7m)

電磁頭:

- 24VAC 電磁頭啟動需求電流: 0.41 amp (9.8 VA); 50HZ 模式下吸持電流 0.32amp (7.7VA)

抗衝擊能力:

- 25千伏浪湧電壓衝擊, 使用中出色的抗浪湧能力

頂部維護及抗雜質的底部濾網

- 所有 952 models

Special Features:

- 配備尾部標準噴嘴, 定子自適應調節。



如何訂貨

A	952	XX	XX	XX
介面類型 ACME	型號952	模式 E IC SAM	出廠壓力 (4.8) 80 (5.5)	噴嘴號 44, 48, 52, 56, 60, 64

Descriptive text for understanding only!

Model number would look like A952IC8052 when a customer orders the IC version with a #52 nozzle at a case pressure of 80 PSI



美制單位參數

Dual Spreader™ Nozzles													
	Base Pressure (psi)	#44 - Blue		#48 - Yellow		#52 - Orange		#56 - Green		#60 - Black		#64 - Red	
		Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)
Standard	60	70	19.7	76	27.1	79	31.5	81	35.3	83	38.8	85	42.0
	70	71	21.3	78	29.7	81	34.0	84	38.2	86	42.1	89	47.1
	80	73	22.8	79	31.6	83	36.3	87	41.0	88	44.9	93	48.7
	90	73	23.8	82	33.3	85	38.4	90	42.8	91	47.6	98	51.7
	100	74	25.0	82	35.1	88	40.6	92	45.5	94	49.1	101	54.5
Low Angle	60	70	19.7	77	27.7	78	31.8	82	35.9	81	39.4	—	—
	70	74	21.1	80	30.0	83	34.2	87	38.7	86	42.6	—	—
	80	76	22.9	82	31.5	86	36.6	89	40.9	89	45.6	—	—
	90	77	24.1	84	33.5	87	38.7	90	43.4	92	48.1	—	—
	100	79	25.4	86	35.4	89	40.8	94	46.0	96	51.0	—	—

公制單位參數

Dual Spreader™ Nozzles																			
	基礎壓力 (bar)	#44 - 藍色			#48 - 黃色			#52 - 橘色			#56 - 綠色			#60 - 黑色			#64 - 紅色		
		Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)
Standard	4.1	21.3	4.5	1.24	23.2	6.2	1.71	24.1	7.2	1.99	24.7	8.0	2.23	25.3	8.8	2.45	25.9	9.5	2.65
	4.8	21.6	4.8	1.34	23.8	6.7	1.87	24.7	7.7	2.15	25.6	8.7	2.41	26.2	9.6	2.66	27.1	10.7	2.97
	5.5	22.3	5.2	1.44	24.1	7.2	1.99	25.3	8.2	2.29	26.5	9.3	2.59	26.8	10.2	2.83	28.3	11.1	3.07
	6.2	22.3	5.4	1.50	25.0	7.6	2.10	25.9	8.7	2.42	27.4	9.7	2.70	27.7	10.8	3.00	29.9	11.7	3.26
	6.9	22.6	5.7	1.58	25.0	8.0	2.21	26.8	9.2	2.56	28.0	10.3	2.87	28.7	11.2	3.10	30.8	12.4	3.44
Low Angle	4.1	21.3	4.5	1.24	23.5	6.3	1.75	23.8	7.2	2.01	25.0	8.2	2.26	24.7	8.9	2.49	—	—	—
	4.8	22.6	4.8	1.33	24.4	6.8	1.89	25.3	7.8	2.16	26.5	8.8	2.44	26.2	9.7	2.69	—	—	—
	5.5	23.2	5.2	1.44	25.0	7.2	1.99	26.2	8.3	2.31	27.1	9.3	2.58	27.1	10.4	2.88	—	—	—
	6.2	23.5	5.5	1.52	25.6	7.6	2.11	26.5	8.8	2.44	27.4	9.9	2.74	28.0	10.9	3.03	—	—	—
	6.9	24.1	5.8	1.60	26.2	8.0	2.23	27.1	9.3	2.57	28.7	10.4	2.90	29.3	11.6	3.22	—	—	—

Rain Bird Corporation
6991 E. Southpoint Road
Tucson, AZ 85756
Phone: (520) 741-6100
Fax: (520) 741-6522

Rain Bird Corporation
970 West Sierra Madre Avenue
Azusa, CA 91702
Phone: (626) 812-3400
Fax: (626) 812-3411

Rain Bird International, Inc.
1000 West Sierra Madre Ave.
Azusa, CA 91702
Phone: (626) 963-9311
Fax: (626) 852-7343

Rain Bird Technical Services
(800) RAINBIRD (1-800-724-6247)
(U.S. and Canada)

Specification Hotline
800-458-3005 (U.S. and Canada)

The Intelligent Use of Water™
www.rainbird.com